

torqualizer® series

sports, diagnostics, medical and rehabilitation ergometer series



reliable ergometers made in germany

German Engineering since 1988



torqualizer® cycle ef med 900 with 7" TFT touch display



stainless steel length adjustable cranks [cos30021ef-acr] for an easy and tool-free adaption of the ergometer available at extra charge



horizontal seat adjustment allows a perfect adjustment of the recumbent ergometer to the individual needs for small and tall patients

Benefit from our experience since 1988 in building and servicing standard and customized solutions around the globe.

h/p/cosmos standard

h/p/cosmos has been developing and building treadmills since 1988 in Germany for various fields including fitness, competitive sports, sports medicine, orthopaedic and neurological rehabilitation, sport science, biomechanics, uniformed services, performance diagnostics, cardiopulmonary diagnostics and rehabilitation. This experience, maximum standards in quality and advanced technology are the foundation of our business and reflect in every h/p/cosmos product.

The torqualizer® series with the latest emotion-fitness 900 UserTerminal is the perfect addition to the existing portfolio of treadmills to support therapists and trainers with a matching series of reliable ergometers for professional use. Correspondingly, all components are manufactured in best quality, jointly creating reliable and durable ergometers. The outstanding level of h/p/cosmos products and services as well as attractive prices form the h/p/cosmos standard.

The perfect match for your cardio circle

To allow a seamless look and feel as well as a perfect integration of h/p/cosmos treadmills into a torqualizer® cardio circle, the pluto® ef med treadmill is equipped with the same emotion-fitness 900 UserTerminal as the torqualizer® ergometer series.

Your advantages

All torqualizer® 900 ergometers can be ordered according to the planned application either as sports or medical devices (MDD 93/42/EEC certified with CE labeling) and the treadmill pluto® ef med 900 will be released already with the new certification MDR (EU) 2017/745.

With a keen eye on therapeutic demands, a very low step through allows easy access to the ergometers for patients with limited mobility. The 7" TFT touch display with biofeedback indications is easy to handle, clearly readable and grid independent (except for treadmills or when ordering 24 Volt permanent power supply option).

Customer-specific configuration for individual solutions

Ergometers off the peg can be many, at h/p/cosmos you can also get your individualized torqualizer® ergometer with a large selection of options and accessories.

Various options and preconfigured packages allow you to customize your ergometer for your planned applications.

torqualizer® 900 series programs

With each product of the torqualizer® 900 series, a basic package with three programmes comes pre-installed on your terminal. The quickstart functionality lets you immediately start with manual adjustments according to your needs. The time-programme finishes your training after a certain, predefined time. The pulse programme lets you put in your target pulse/heart rate to be reached within your training session. Until this pulse is reached, the training difficulty advances.



Programme package additionally includes:

- Programmes: Watt sensitive, Isokinetic*, Therapy, Interval, K-Cal, Hills, Distance
 - Tests for torqualizer® cycle ef (med) 900: IPN, PWC, Astrand, Standard Test, Lactate, Conconi 50, Conconi 100
 - Systems for torqualizer® cycle ef (med) 900, recumbent ef (med) 900 & cross ef (med) 900: motion balance system, Serious Games (Slalom, Freeway, Balance)
- *not available for torqualizer® stair



Connect package includes

- RFID, NFC connectivity - easy nearfield access for different devices
- Simple connection with compatible mobile devices
- Bluetooth® Low Energy connection
- Barcode identification for easy scan & connect




Performance package includes

- Charging with wireless Qi-inductive technology for many compatible smart devices
- Higher maximum power for extensive training
- Reduced initial load of 7 watts (cycle, recumbent, body) or 15 watts (cross) when using an external power supply



All-in package includes


- Programme package
- Connect package
- Performance package





program / test	standard package	programme package for torqualizer® 900 series	
quick time			
pulse			
watt sensitive		pluto ef (med) 900	
isokinetic*		arm ef (med) 900	
therapy		arm ef (med) 900-wm	
interval		stair ef (med) 900	
K-Cal			cross ef (med) 900
Hills			recumbent ef (med) 900
Distance			
Motion balance system			cycle ef (med) 900
Serious Games			
IPN			
PWC			
Astrand			
Standard			
Lactate			
Conconi 50			
Conconi 100			


*not available for torqualizer® stair


Overview of the torqualizer® series:


	bike-ergometer	torqualizer® cycle ef med 900	torqualizer® cycle ef 900
	order number	cos30021ef-med900	cos30021ef-900
	applications	endurance training cycling	
	functions	7" TFT - capacitive multicolor touch display, high resolution, biofeedback, low step through / easy access, horizontally and vertically adjustable saddle, hybrid POLAR® pulse receiver, optional Bluetooth®, NFC, RFID, optional inductive charging for mobile devices	
	power range*	standard: 15 (med) / 25 (sport) ... 500 watts rpm independent (up to 1,000 watts rpm dependent) optional: 15 (med) / 25 (sport) ... 950 watts rpm independent (up to 1,000 watts rpm dependent)	

	recumbent-ergometer	torqualizer® recumbent ef med 900	torqualizer® recumbent ef 900
	order number	cos30031ef-med900	cos30031ef-900
	applications	endurance training legs / obese trainees / long training sessions	
	functions	7" TFT - capacitive multicolor touch display, high resolution, biofeedback, low step through easy access; horizontal seat adjustment, adjustable backrest, hybrid POLAR® pulse receiver, optional Bluetooth®, NFC, RFID, optional inductive charging for mobile devices	
	power range*	standard: 15 (med) / 25 (sport) ... 500 watts rpm independent (up to 1000 watts rpm dependent) optional: 15 (med) / 25 (sport) ... 950 watts rpm independent (up to 1000 watts rpm dependent)	

	arm-ergometer	torqualizer® arm ef med 900	torqualizer® arm ef 900
	order number	cos30030ef-med900	cos30030ef-900
	applications	endurance training, mobilisation & stabilisation of upper body / arms	
	functions	7" TFT - capacitive multicolor touch display, high resolution, biofeedback, gas pressure supported height adjustment of the drive unit, length-adjustable crank arms, synchronous & asynchronous mode, long seat for optimal positioning, easy dismantling of the seat for wheelchair access, rpm dependent and independent mode, hybrid POLAR® pulse receiver, optional Bluetooth®, NFC, RFID, optional inductive charging for mobile devices	
	power range*	standard: 15 (med) / 25 (sport) ... 500 watts rpm independent (up to 1,000 watts rpm dependent) optional: 15 (med) / 25 (sport) ... 950 watts rpm independent (up to 1,000 watts rpm dependent)	

	cross-ergometer	torqualizer® cross ef med 900	torqualizer® cross ef 900
	order number	cos30032ef-med900	cos30032ef-900
	applications	full body endurance training, easy on the joints	
	functions	7" TFT - capacitive multicolor touch display, high resolution, biofeedback forwards and backwards movement, hybrid POLAR® pulse receiver, rpm limit adjustable for extra safety, optional Bluetooth®, NFC, RFID, inductive charging for mobile devices	
	power range*	standard: 100 ... 500 watts rpm independent (up to 1,000 watts rpm dependent) optional: 100 ... 950 watts rpm independent (up to 1,000 watts rpm dependent)	

	stair-ergometer	torqualizer® stair ef med 900	torqualizer® stair ef 900
	order number	cos30033ef-med900	cos30033ef-900
	applications	endurance training legs / coordination / activity of daily life (ADL)	
	functions	7" TFT - capacitive multicolor touch display, high resolution, biofeedback, POLAR® auto connection system (Bluetooth® Low Energy & 5kHz), pedal independent system, cushioned pedal suspension, automatic weight detection for precise calculation of performance, optional Bluetooth®, NFC, RFID, optional inductive charging for mobile devices	

	treadmill	pluto® ef med 900	pluto® ef 900
	order number	cos31012	cos31011
	applications	endurance training walking and running, stress device for performance testing, gait analysis and gait training	endurance training walking and running
	functions	7" TFT - capacitive multicolor touch display, high resolution, biofeedback, POLAR® auto connection system (Bluetooth® Low Energy & 5kHz), optional Bluetooth®, NFC, RFID, optional inductive charging for mobile devices	

*Power range of all medical torqualizers®: 15 ... 500 watts rpm independent (cross ef med: 100 ... 500 watts rpm independent); 7 watts minimum resistance if the optional 24 Volt permanent power supply option is used, 15 (med) / 25 (sport) ... 950 watts independent (cross ef med 100 ... 950 Watt rpm independent) with performance package (optional 1000 watt rpm dependent at extra charge)

configuration torqualizer® ef med 900: therapy basic

recommended configuration therapy basic torqualizer® ef med 900



pos.	qty.	order number	product description
1.	1	cos30021ef-med900	torqualizer® cycle ef med 900 hybrid brake system with 15 ... 500 watts, 15 ... 140 rpm, max. user weight 150kg 7" TFT - capacitive multicolor touch display, high resolution, biofeedback
2.	1	cos30021ef-pro	Programme package for series 900 - Plus 7 programs, IPN Test, plus 5 additional tests, full range of functions on motion balance system and serious games
3.	1	cos30021-B-EF-AL-188	Packing torqualizer® for bicycle ef (med) 900 , (L: 125 cm / W: 85 cm / H: 170 cm) packed fully assembled on pallet with metal frame and cardboard hood for bicycle-ergometer
4.	1	cos104392	transport / shipping charge (please specify if truck, sea or air freight; for overseas, sea shipment is recommended)
5.	1	cos15732-os	installation, commissioning and instruction through authorized and trained personnel

E & OE. Subject to alterations without prior notice. The illustrations may show accessories and items of optional equipment which are not part of standard specification or the recommended configuration.
Subject to our general terms of trade: www.hpccosmos.com

configuration torqualizer® ef med 900: cardiac testing and training

recommended configuration cardiac testing and training torqualizer® ef med 900



pos.	qty.	order number	product description
1.	1	cos30021ef-med900	torqualizer® cycle ef med 900 hybrid brake system with 15 ... 500 watts, 15 ... 140 rpm, max. user weight 150kg 7" TFT - capacitive multicolor touch display, high resolution, biofeedback
2.	1	cos30021ef-per	All-in Package (includes Performance package with extended max. workload - 950 watts, Programme Package & Connect Package)
3.	1	cos30021ef-900-epc	Power supply for power connection - Power supply 24 Volt
4.	1	cos30021-B-EF-AL-188	Packing torqualizer® for bicycle ef (med) 900 , (L: 125 cm / W: 85 cm / H: 170 cm) packed fully assembled on pallet with metal frame and cardboard hood for bicycle-ergometer
5.	1	cos104392	transport / shipping charge (please specify if truck, sea or air freight; for overseas, sea shipment is recommended)
6.	1	cos15732-os	installation, commissioning and instruction through authorized and trained personnel

E & OE. Subject to alterations without prior notice. The illustrations may show accessories and items of optional equipment which are not part of standard specification or the recommended configuration.
Subject to our general terms of trade: www.hpccosmos.com

configuration torqualizer® recumbent ef med 900: therapy basic

recommended configuration therapy basic torqualizer® recumbent ef med 900




pos.	qty.	order number	product description
1.	1	cos30031ef-med900	torqualizer® recumbent ef med 900 hybrid brake system with 15 ... 500 watts, 20 ... 120 rpm, max. user weight 150kg 7" TFT - capacitive multicolor touch display, high resolution, biofeedback
2.	1	cos30021ef-pro	Programme package for medical devices - Plus 7 programmes, IPN Test, plus 5 additional tests, full range of functions on motion balance system and serious games
3.	1	cos30031-B-EF-AL-189	Packing torqualizer® for recumbent ef (med) 900 , (L: 217 cm / W: 79 cm / H: 155 cm) packed fully assembled on pallet with metal frame and cardboard hood for bicycle-ergometer
4.	1	cos104392	transport / shipping charge (please specify if truck, sea or air freight; for overseas, sea shipment is recommended)
5.	1	cos15732-os	installation, commissioning and instruction through authorized and trained personnel

E & OE. Subject to alterations without prior notice. The illustrations may show accessories and items of optional equipment which are not part of standard specification or the recommended configuration.
Subject to our general terms of trade: www.hpccosmos.com

configuration pluto® ef med: rehabilitation and diagnostics

To allow a seamless look and feel for therapists and patients as well as a perfect integration of h/p/cosmos treadmills into a torqualizer® cardio circle, the pluto® ef med treadmill is equipped with the same user terminal as the torqualizer® series. The specific terminal must be originally equipped and cannot be retrofitted to existing pluto® treadmills. Many further h/p/cosmos accessories (e.g. different handrails, safety or unweighting systems) can be retrofitted.



recommended configuration rehabilitation and diagnostics pluto® ef med

pos.	qty.	order number	product description
1.	1	cos31012	pluto® ef med running surface 150 x 50 cm, speed range 0 ... 22 km/h, elevation 0 ... 25 %, max. user weight 250 kg (optional up to 300 kg available) 7" TFT - capacitive multicolor touch display, high resolution
2.	1	cos10079-01va01	Safety arch 50 with harness & chest belt / stop function, fall protection for all applications (mandatory for high risk applications); running surface 50 cm wide
3.	1	cos102522va03	Packing treadmill 150/50 (SA) , packed part assembled on pallet with cardboard hood, incl. safety arch (L: 274 cm / W: 122 cm / H: 94 cm)
4.	1	cos104392	transport / shipping charge (please specify if truck, sea or air freight; for overseas sea shipment is recommended)
5.	1	cos15732-os	installation, commissioning and instruction through authorized and trained personnel

E & OE. Subject to alterations without prior notice. The illustrations may show accessories and items of optional equipment which are not part of standard specification or the recommended configuration. Subject to our general terms of trade: www.hpcosmos.com


Our recommended upgrades for pluto® ef med:



adjustable handrails [cos102010va05] allow an easy, fast and tool-free adaptation of the handrail height and width



standard maximum user weight of 250 kg can optionally be upgraded to 300 kg max. user weight



the optional connect package [cos30021ef-con] allows wireless (RFID, NFC, Bluetooth, Barcode) transmission of training data to compatible PC software

torqualizer® 1200

Ergometer for endurance training and cycling. Stress device for performance testing with up to 950 watts resistance.

The torqualizer® 1200 ergometer is a brand new development by h/p/cosmos based on proven technologies and designs in combination with modern features. A clear focus on ergonomics, market requirements and state of the art technology has driven the development.

With our long history and experience in the development and manufacturing of treadmills, it was time to extend our position as reliable supplier for training and medical testing devices to the field of bike ergometers. The torqualizer® 1200 comes with the well-established MCU6 UserTerminal, granting a similar design, look & feel and related features known from the h/p/cosmos MCU6 treadmill series pluto®, mercury®, quasar® and pulsar®. Among the key features of the torqualizer series are the rigid construction, the fully adjustable frame including adjustable step through and of course the interface known from the current generation of treadmills that includes graphic display of heart rate variability via Poincaré diagram.

The torqualizer® 1200 (med) are currently in the latest stages of development, testing and certification and will be launched to the market approx. in early 2025.



torqualizer® 1200

Ergometer for endurance training and cycling. Stress device for performance testing with up to 950 watts resistance.



Adjustable saddle posts and handlebars for maximum flexibility and individualization for therapeutic and athletic applications



exchangeable handlebars and adjustable handlebar position



Gridless horizontal saddle adjustment with conveniently changeable saddle for sports [cos104528] or therapy



For therapeutic applications, a specially designed saddle and handlebar [cos104071va01] are available for comfortable and upright sitting.



Height and width adjustments of frame, saddle and handlebar provide flexibility for a maximum versatility for small and tall athletes or patients.



deep step through and rigid frame construction



Q-factor of 0.9 allows (depending on pedals mounted) ergonomic cycling for athletes and patients


specifications torqualizer® 1200 med
(certification pending / Product launch planned for 2025)

specifications torqualizer® 1200 sport
(certification pending / Product launch planned for 2025)

bike-ergometer	torqualizer® 1200 med	torqualizer® 1200 sport
manufacturer:	h/p/cosmos sports & medical gmbh / Germany	h/p/cosmos sports & medical gmbh / Germany
order number:	cos30021va02	cos30021va01
applications:	endurance training cycling, stress device for performance testing	endurance training cycling
functions:	easy to handle, 10.1" LCD touch display, high resolution coloured display with Bio-Feedback; easy step-through, horizontally and vertically adjustable saddle	easy to handle, 10.1" LCD touch display, high resolution coloured display with Bio-Feedback; easy step-through horizontally and vertically adjustable saddle
max. user weight:	150 kg / 330 lbs (optional 200 kg / 440 lbs available at extra charge)	150 kg / 330 lbs (optional 200 kg / 440 lbs available at extra charge)
voltage supply:	230 V	230 V
control:	via UserTerminal with keyboard & display	via UserTerminal with keyboard & display
power range:	7 ... 950 watts rpm independent	7 ... 950 watts rpm independent
speed range:	20 ... 140 rpm	20 ... 140 rpm
brake:	hybrid-brake-system (HBS)	hybrid-brake-system (HBS)
safety:	CE 0123; MDR (EU) 2017/745, DIN EN ISO 20957-1; DIN EN ISO 20957-5; DIN EN 60601-1; DIN EN 60601-1-2; Not UL-certified. Certification pending. Product launch planned for 2025	CE; DIN EN ISO 20957-1; DIN EN ISO 20957-5; DIN EN 60601-1-2; Not UL-certified. Certification pending. Product launch planned for 2025
classification:	medical device risk class IIa according to MDR, therapeutic medical device and diagnostic medical device Certification pending. Product launch planned for 2025	sports and fitness device; not for medical, not for therapeutical applications Certification pending. Product launch planned for 2025
usage class:	S, I according to ISO 20957-5	S, I according to ISO 20957-5
accuracy class:	A (high accuracy) according to DIN EN ISO 20957-1	A (high accuracy) according to DIN EN ISO 20957-1
digital interface:	optional Bluetooth®, NFC, RFID	optional Bluetooth®, NFC, RFID
programs:	quick start, time, pulse, optional program package available	quick start, time, pulse, optional program package available
colour of frame:	pure white RAL 9010 (powder coated)	pure white RAL 9010 (powder coated)
size of frame:	L x W x H: 150 x 70 x 130 cm (4ft 9.2" x 2ft 2.9" x 4ft 26")	L x W x H: 150 x 70 x 130 cm (4ft 9.2" x 2ft 2.9" x 4ft 26")
net. weight:	device approx. 110 kg (243 lbs)	device approx. 110 kg (243 lbs)
gross weight:	depending on package mode chosen (land, sea, air)	depending on package mode chosen (land, sea, air)

Weight and dimensions may differ depending on accessories.

E & OE. Subject to alterations without prior notice. The illustrations may show accessories and items of optional equipment which are not part of standard specification or the recommended configuration. Subject to our general terms of trade: www.hpcosmos.com



specifications torqualizer® ef med 900

specifications torqualizer® ef 900

bike-ergometer	torqualizer® cycle ef med 900	torqualizer® cycle ef 900
manufacturer:	emotion fitness GmbH & Co. KG / Germany	emotion fitness GmbH & Co. KG / Germany
order number:	cos30021ef-med900	cos30021ef-900
applications:	endurance training cycling, stress device for performance testing	endurance training cycling, stress device for performance testing
functions:	7" TFT – capacitive touch display, high resolution coloured display with Bio-Feedback; easy step-through; easy to handle; horizontally and vertically adjustable saddle; Polar® - auto connection system	7" TFT – capacitive touch display, high resolution coloured display with Bio-Feedback; easy step-through; easy to handle; horizontally and vertically adjustable saddle; Polar® - auto connection system
max. user weight:	150 kg / 330 lbs (optional 200 kg / 440 lbs available at extra charge)	150 kg / 330 lbs (optional 200 kg / 440 lbs available at extra charge)
voltage supply:	torqualizer® ergometer is grid independent, except when ordering 24 Volt permanent power supply option	torqualizer® ergometer is grid independent, except when ordering 24 Volt permanent power supply option
control:	via UserTerminal with keyboard & display	via UserTerminal with keyboard & display
power range:	15 ... 500 watts rpm independent (up to 1,000 watts rpm dependent) 15 ... 950 watts rpm independent (up to 1,000 watts rpm dependent) at extra charge starting from 7 watts with additional external power supply	25 ... 500 watts rpm independent (up to 1,000 watts rpm dependent) 25 ... 950 watts rpm independent (up to 1,000 watts rpm dependent) at extra charge starting from 7 watts with additional external power supply
speed range:	15 ... 140 rpm	15 ... 140 rpm
brake:	hybrid-brake-system (HBS)	hybrid-brake-system (HBS)
safety:	CE 0633; MDD 93/42/EEC, Class IIa, DIN EN ISO 20957-1; DIN EN ISO 20957-5; DIN EN 60601-1; DIN EN 60601-1-2; Not UL-certified. Device not for sale in Canada and the USA.	CE; DIN EN ISO 20957-1; DIN EN ISO 20957-5; Not UL-certified. Device not for sale in Canada and the USA.
classification:	medical device risk class IIa according to MDD, therapeutic medical device and diagnostic medical device	sports and fitness device; not for medical, not for therapeutical applications
usage class:	S, I according to ISO 20957-1	S, I according to ISO 20957-1
accuracy class:	A (high accuracy) according to DIN EN ISO 20957-1	A (high accuracy) according to DIN EN ISO 20957-1
digital interface:	optional Bluetooth®, NFC, RFID	optional Bluetooth®, NFC, RFID
programs:	quick start, time, pulse, optional program package available	quick start, time, pulse, optional program package available
colour of frame:	white aluminum RAL 9006 (powder coated)	white aluminum RAL 9006 (powder coated)
size of frame:	L x W x H: 119 x 65 x 145 cm (3ft 10.85" x 2ft 1.6" x 4ft 9")	L x W x H: 119 x 65 x 145 cm (3ft 10.85" x 2ft 1.6" x 4ft 9")
net. weight:	device approx. 58 kg (128 lbs)	device approx. 58 kg (128 lbs)
gross weight:	depending on package mode chosen (land, sea, air)	depending on package mode chosen (land, sea, air)

Weight and dimensions may differ depending on accessories.

E & OE. Subject to alterations without prior notice. The illustrations may show accessories and items of optional equipment which are not part of standard specification or the recommended configuration.

Subject to our general terms of trade: www.hpcosmos.com



specifications torqualizer® arm ef med 900

specifications torqualizer® arm ef 900

arm-ergometer	torqualizer® arm ef med 900	torqualizer® arm ef 900
manufacturer:	emotion fitness GmbH & Co. KG / Germany	emotion fitness GmbH & Co. KG / Germany
order number:	cos30030ef-med900	cos30030ef-900
applications:	endurance training upper body / arms	endurance training upper body / arms
functions:	easy to handle, 7" TFT – capacitive touch display, high resolution coloured display with Bio-Feedback; easy step-through, easily removable seat; length adjustable crank arm (with synchronous mode), bi-directional drive; Polar® - auto connection system	easy to handle, 7" TFT – capacitive touch display, high resolution coloured display with Bio-Feedback; easy step-through, easily removable seat; length adjustable crank arm (with synchronous mode), bi-directional drive; Polar® - auto connection system
max. user weight:	150 kg / 330 lbs (optional 200 kg / 440 lbs available at extra charge)	150 kg / 330 lbs (optional 200 kg / 440 lbs available at extra charge)
voltage supply:	torqualizer® ergometer is grid independent, except when ordering 24 Volt permanent power supply option	torqualizer® ergometer is grid independent, except when ordering 24 Volt permanent power supply option
control:	via UserTerminal with keyboard & display	via UserTerminal with keyboard & display
power range:	15 ... 500 watts rpm independent (up to 1,000 watts rpm dependent) 15 ... 550 watts rpm independent (up to 1,000 watts rpm dependent) at extra charge starting from 7 watts with additional external power supply	25 ... 500 watts rpm independent (up to 1,000 watts rpm dependent) 25 ... 550 watts rpm independent (up to 1,000 watts rpm dependent) at extra charge starting from 7 watts with additional external power supply
speed range:	15 ... 140 rpm	15 ... 140 rpm
brake:	hybrid-brake-system (HBS)	hybrid-brake-system (HBS)
safety:	CE 0633; MDD 93/42/ECC, Class IIa, DIN EN ISO 20957-1; DIN EN ISO 20957-5; DIN EN 60601-1; DIN EN 60601-1-2; Not UL-certified. Device not for sale in Canada and the USA.	CE; DIN EN ISO 20957-1; DIN EN ISO 20957-5; Not UL-certified. Device not for sale in Canada and the USA.
classification:	medical device risk class IIa according to MDD, therapeutic medical device and diagnostic medical device	sports and fitness device; not for medical, not for therapeutic applications
usage class:	S, I according to ISO 20957-1	S, I according to ISO 20957-1
accuracy class:	A (high accuracy) according to DIN EN ISO 20957-1	A (high accuracy) according to DIN EN ISO 20957-1
digital interface:	optional Bluetooth®, NFC, RFID	optional Bluetooth®, NFC, RFID
programs:	quick start, time, pulse, optional program package available	quick start, time, pulse, optional program package available
colour of frame:	white aluminum RAL 9006 (powder coated)	white aluminum RAL 9006 (powder coated)
size of frame:	L x W x H: 116 x 77 x 155 cm (3ft 9.6" x 2ft 6.3" x 5ft 1")	L x W x H: 116 x 77 x 155 cm (3ft 9.6" x 2ft 6.3" x 5ft 1")
net. weight:	device approx. 98 kg (216.1 lbs)	device approx. 98 kg (216.1 lbs)

Weight and dimensions may differ depending on accessories.

E & OE. Subject to alterations without prior notice. The illustrations may show accessories and items of optional equipment which are not part of standard specification or the recommended configuration. Subject to our general terms of trade: www.hpcosmos.com



specifications torqualizer® recumbent ef med 900

specifications torqualizer® recumbent ef 900

bike-ergometer	torqualizer® recumbent med 900	torqualizer® recumbent 900
manufacturer:	emotion fitness GmbH & Co. KG / Germany	emotion fitness GmbH & Co. KG / Germany
order number:	cos30031ef-med900	cos30031ef-900
applications:	endurance training legs, obese patients, long training session	endurance training legs, obese trainees, long training session
functions:	7" TFT – capacitive touch display, high resolution coloured display, with biofeedback, easy access, horizontal seat adjustment, adjustable backrest, grid independent, Polar® - auto connection system	7" TFT – capacitive touch display, high resolution coloured display, with biofeedback, easy access, horizontal seat adjustment, adjustable backrest, grid independent, Polar® - auto connection system
max. user weight:	150 kg (330 lbs), optional 200 / 250 kg (440 / 551 lbs) available at extra charge	150 kg (330 lbs), optional 200 / 250 kg (440 / 551 lbs) available at extra charge
voltage supply:	torqualizer® ergometer is grid independent, except when ordering 24 Volt permanent power supply option	torqualizer® ergometer is grid independent, except when ordering 24 Volt permanent power supply option
control:	via UserTerminal with keyboard & display	via UserTerminal with keyboard & display
power range:	15 ... 500 watts rpm independent (up to 1,000 watts rpm dependent) 15 ... 950 watts rpm independent (up to 1,000 watts rpm dependent) at extra charge starting from 7 watts with additional external power supply	25 ... 500 watts rpm independent (up to 1,000 watts rpm dependent) 25 ... 950 watts rpm independent (up to 1,000 watts rpm dependent) at extra charge starting from 7 watts with additional external power supply
speed range:	15 ... 140 rpm	15 ... 140 rpm
brake:	hybrid-brake-system (HBS)	hybrid-brake-system (HBS)
safety:	CE 0633; MDD 93/42/EEC, Class IIa, DIN EN ISO 20957-1; DIN EN ISO 20957-5; DIN EN 60601-1; DIN EN 60601-1-2; Not UL-certified. Device not for sale in Canada and the USA.	CE; DIN EN ISO 20957-1; DIN EN ISO 20957-5; DIN EN 60601-1-2. Not UL-certified. Device not for sale in Canada and the USA.
classification:	medical device risk class IIa according to MDD, therapeutic medical device and diagnostic medical device	sports and fitness device; not for medical, not for therapeutic applications
usage class:	S, I according to ISO 20957-1	S, I according to ISO 20957-1
accuracy class:	A (high accuracy) according to DIN EN ISO 20957-1	A (high accuracy) according to DIN EN ISO 20957-1
digital interface:	optional Bluetooth®, NFC, RFID	optional Bluetooth®, NFC, RFID
programs:	quick start, time, pulse, optional therapy package available	quick start, time, pulse, optional therapy package available
colour of frame:	white aluminum RAL 9006 (powder coated)	white aluminum RAL 9006 (powder coated)
size of frame:	L x W x H: 173 x 65 x 133 cm (5ft 8.11" x 2ft 1.59" x 4ft 4.36") L x W x H with boosted 250 kg: 173 x 78 x 133 cm (5ft 8.11" x 2ft 6.7" x 4ft 4.36")	L x W x H: 173 x 65 x 133 cm (5ft 8.11" x 2ft 1.59" x 4ft 4.36") L x W x H with boosted 250 kg: 173 x 78 x 133 cm (5ft 8.11" x 2ft 6.7" x 4ft 4.36")
net. weight:	device approx. 80 kg (176.4 lbs) with boosted 250 kg: approx. 104 kg (230lbs)	device approx. 80 kg (176.4 lbs) with boosted 250 kg: approx. 104 kg (230lbs)

Weight and dimensions may differ depending on accessories.

E & OE. Subject to alterations without prior notice. The illustrations may show accessories and items of optional equipment which are not part of standard specification or the recommended configuration. Subject to our general terms of trade: www.hpcosmos.com



specifications torqualizer® arm ef med 900 wall model

specifications torqualizer® arm ef 900 wall model

arm-ergometer	torqualizer® arm ef med 900 wall model	torqualizer® arm ef 900 wall model
manufacturer:	emotion fitness GmbH & Co. KG / Germany	emotion fitness GmbH & Co. KG / Germany
order number:	cos30030ef-med900-wm	cos30030ef-900-wm
applications:	endurance training upper body / arms	endurance training upper body / arms
functions:	easy to handle, 7" TFT – capacitive touch display, high resolution coloured display with Bio-Feedback; length adjustable crank arm (with synchronous mode), bi-directional drive; Polar® - auto connection system	easy to handle, 7" TFT – capacitive touch display, high resolution coloured display with Bio-Feedback; length adjustable crank arm (with synchronous mode), bi-directional drive; Polar® - auto connection system
voltage supply:	torqualizer® ergometer is grid independent, except when ordering 24 Volt permanent power supply option	torqualizer® ergometer is grid independent, except when ordering 24 Volt permanent power supply option
control:	via UserTerminal with keyboard & display	via UserTerminal with keyboard & display
power range:	15 ... 500 watts rpm independent (up to 1,000 watts rpm dependent) 15 ... 550 watts rpm independent (up to 1,000 watts rpm dependent) starting from 7 watts with additional external power supply	25 ... 500 watts rpm independent (up to 1,000 watts rpm dependent) 25 ... 550 watts rpm independent (up to 1,000 watts rpm dependent) at extra charge starting from 7 watts with additional external power supply
speed range:	15 ... 140 rpm	15 ... 140 rpm
brake:	hybrid-brake-system (HBS)	hybrid-brake-system (HBS)
safety:	CE 0633; MDD 93/42/ECC, Class IIa, DIN EN ISO 20957-1; DIN EN ISO 20957-5; DIN EN 60601-1; DIN EN 60601-1-2; Not UL-certified. Device not for sale in Canada and the USA.	CE; DIN EN ISO 20957-1; DIN EN ISO 20957-5; Not UL-certified. Device not for sale in Canada and the USA.
classification:	medical device risk class IIa according to MDD, therapeutic medical device and diagnostic medical device	sports and fitness device; not for medical, not for therapeutic applications
usage class:	S, I according to ISO 20957-1	S, I according to ISO 20957-1
accuracy class:	A (high accuracy) according to DIN EN ISO 20957-1	A (high accuracy) according to DIN EN ISO 20957-1
digital interface:	optional Bluetooth®, NFC, RFID	optional Bluetooth®, NFC, RFID
programs:	quick start, time, pulse, optional program package available	quick start, time, pulse, optional program package available
colour of frame:	white aluminum RAL 9006 (powder coated)	white aluminum RAL 9006 (powder coated)
size of frame:	L x W x H: 63 x 56 x 155 cm (2ft 0.8" x 1ft 10" x 5ft 1")	L x W x H: 63 x 56 x 155 cm (2ft 0.8" x 1ft 10" x 5ft 1")
net. weight:	device approx. 48 kg (105.9 lbs)	device approx. 48 kg (105.9 lbs)

Weight and dimensions may differ depending on accessories.

E & OE. Subject to alterations without prior notice. The illustrations may show accessories and items of optional equipment which are not part of standard specification or the recommended configuration.

Subject to our general terms of trade: www.hpcosmos.com



specifications torqualizer® cross ef med 900

specifications torqualizer® cross ef 900

cross-ergometer	torqualizer® cross med 900	torqualizer® cross 900
manufacturer:	emotion fitness GmbH & Co. KG / Germany	emotion fitness GmbH & Co. KG / Germany
order number:	cos30032ef-med900	cos30032ef-900
applications:	full body endurance training, easy on the joints	full body endurance training, easy on the joints
functions:	7" TFT – capacitive touch display, high resolution coloured display with Bio-Feedback; easy step-through; easy to handle; horizontally and vertically adjustable saddle; Polar® - auto connection system	7" TFT – capacitive touch display, high resolution coloured display with Bio-Feedback; easy step-through; easy to handle; horizontally and vertically adjustable saddle; Polar® - auto connection system
max. user weight:	150 kg / 330 lbs (optional 200 kg / 440 lbs available at extra charge)	150 kg / 330 lbs (optional 200 kg / 440 lbs available at extra charge)
voltage supply:	torqualizer® ergometer is grid independent, except when ordering 24 Volt permanent power supply option	torqualizer® ergometer is grid independent, except when ordering 24 Volt permanent power supply option
control:	via UserTerminal with keyboard & display	via UserTerminal with keyboard & display
power range:	100 ... 500 watts rpm independent (up to 1,000 watts rpm dependent) 100 ... 950 watts rpm independent with performance package starting from 7 watts with additional external power supply optional display of brake wattage with 15 watts initial break resistance;	100 ... 500 watts rpm independent (up to 1,000 watts rpm dependent) 100 ... 950 watts rpm independent with performance package starting from 7 watts with additional external power supply optional display of brake wattage with 15 watts initial break resistance;
speed range:	15 ... 140 rpm	15 ... 140 rpm
brake:	hybrid-brake-system (HBS)	hybrid-brake-system (HBS)
safety:	CE 0633; MDD 93/42/ECC, Class IIa, DIN EN ISO 20957-1; DIN EN ISO 20957-9; DIN EN 60601-1; DIN EN 60601-1-2; Not UL-certified. Device not for sale in Canada and the USA.	CE; DIN EN ISO 20957-1; DIN EN ISO 20957-9; Not UL-certified. Device not for sale in Canada and the USA.
classification:	medical device risk class IIa according to 93/42 EEC, therapeutic medical device and diagnostic medical device	sports and fitness device; not for medical, not for therapeutic applications
usage class:	S, I according to ISO 20957-1	S, I according to ISO 20957-1
accuracy class:	A (high accuracy) according to DIN EN ISO 20957-1	A (high accuracy) according to DIN EN ISO 20957-1
digital interface:	optional Bluetooth®, NFC, RFID	optional Bluetooth®, NFC, RFID
programs:	quick start, time, heart rate, optional therapy package available	quick start, watts, heart rate, optional comfort package available
colour of frame:	white aluminum RAL 9006 (powder coated)	white aluminum RAL 9006 (powder coated)
size of frame:	L x W x H: 200 x 65 x 169 cm (6ft 6.7" x 2ft 1.5" x 5ft 6.5")	L x W x H: 200 x 65 x 169 cm (6ft 6.7" x 2ft 1.5" x 5ft 6.5")
net. weight:	device approx. 101 kg (223 lbs)	device approx. 101 kg (223 lbs)

Weight and dimensions may differ depending on accessories.

E & OE. Subject to alterations without prior notice. The illustrations may show accessories and items of optional equipment which are not part of standard specification or the recommended configuration. Subject to our general terms of trade: www.hpcosmos.com



specifications torqualizer® stair ef med 900

specifications torqualizer® stair ef 900

stair-ergometer	torqualizer® stair ef med 900	torqualizer® stair ef 900
manufacturer:	emotion fitness GmbH & Co. KG / Germany	emotion fitness GmbH & Co. KG / Germany
order number:	cos30033ef-med900	cos30033ef-900
applications:	endurance training legs, coordination, activity of daily life (ADL)	endurance training legs, coordination, activity of daily life (ADL)
functions:	7" TFT – capacitive touch display, high resolution coloured display with biofeedback, Polar® - auto connection system, pedal independent system, cushioned pedal suspension, automatic weight detection for precise calculation of performance	7" TFT – capacitive touch display, high resolution coloured display with biofeedback, Polar® - auto connection system, pedal independent system, cushioned pedal suspension, automatic weight detection for precise calculation of performance
max. user weight:	150 kg	150 kg
voltage supply:	torqualizer® ergometer is grid independent, except when ordering 24 Volt permanent power supply option	torqualizer® ergometer is grid independent, except when ordering 24 Volt permanent power supply option
control:	via UserTerminal with keyboard & display	via UserTerminal with keyboard & display
power range:	Isokinetic mode of operation for 4 ... 27 m / min falling speed	Isokinetic mode of operation for 4 ... 27 m / min falling speed
brake:	hybrid-brake-system (HBS)	hybrid-brake-system (HBS)
motor system:	calibrated drive unit	calibrated drive unit
safety:	CE 0633; MDD 93/42/ECC, Class IIa, DIN EN ISO 20957-1; DIN EN ISO 20957-8; DIN EN 60601-1; DIN EN 60601-1-2; Not UL-certified. Device not for sale in Canada and the USA.	CE; DIN EN ISO 20957-1; DIN EN ISO 20957-8; Not UL-certified. Device not for sale in Canada and the USA.
classification:	medical device risk class IIa according to MDD, therapeutic medical device and diagnostic medical device	sports and fitness device; not for medical, not for therapeutic applications
usage class:	S, I according to ISO 20957-1	S, I according to ISO 20957-1
accuracy class:	A (high accuracy) according to DIN EN ISO 20957-1	A (high accuracy) according to DIN EN ISO 20957-1
digital interface:	optional Bluetooth®, NFC, RFID	optional Bluetooth®, NFC, RFID
programs:	quick start, time, pulse, optional program package available	quick start, watts, heart rate, optional program package available
colour of frame:	white aluminum RAL 9006 (powder coated)	white aluminum RAL 9006 (powder coated)
size of frame:	L x W x H: 102 x 73 x 160 cm (3ft 4.1" x 2ft 4.7" x 5ft 3")	L x W x H: 102 x 73 x 160 cm (3ft 4.1" x 2ft 4.7" x 5ft 3")
net. weight:	device approx. 79 kg (175 lbs)	device approx. 79 kg (175 lbs)

Weight and dimensions may differ depending on accessories.

E & OE. Subject to alterations without prior notice. The illustrations may show accessories and items of optional equipment which are not part of standard specification or the recommended configuration. Subject to our general terms of trade: www.hpcosmos.com



specifications pluto® ef med 900 Certification pending. Product launch planned for Q4 2024.

treadmill	pluto® ef med
manufacturer:	h/p/cosmos sports & medical gmbh / Germany
order number:	cos31012
applications:	endurance training walking and running stress device for performance testing, gait analysis and gait training
control:	User Terminal with easy-to-use 7" TFT – capacitive touch display, via integrated interface coscom® v4
running surface:	L x W: 150 x 50 cm (4' 11.1" x 1' 7.6") access height: 23 cm (9.1") - shock load reduction for the joints - running belt with slip resistant surface - max. permissible load: 250 kg (551 lbs) - max. permissible load: 300 kg (660 lbs) at extra charge
speed range:	0.0 ... 22.0 km/h (0.0 ... 6.1 m/s) (0.0 ... 13.7 mph) special speed available at extra charge
acceleration:	1 acceleration / deceleration level
elevation:	0 ... 25 % (0 ... 14.0°) motorized adjustment (-25 % ... +25 % when using optional reverse belt rotation)
running direction:	reverse belt rotation at extra charge. Without fall prevention the max. speed for reverse belt rotation is limited to 5 km/h (3.1 mph)
motor systems:	2.2 kW (3 HP) 3-phase AC motor, maintenance free and brushless For high-performance applications we recommend models with a 3-phase 3x400 Volt power supply and a running surface min. 190/65 cm
power transmission:	frequency inverter, poly-V-belt, very quiet operation
safety systems:	CE 0123; medical device regulation MDR (EU) 2017/745, machinery regulation (EU) 2023/1230; IEC 60601-1; EN 60601-1-2 (EMC tested); ISO 20957-1; ISO 20957-6; EN 14971; emergency-stop mushroom push button (drives power off), emergency-stop with pull cord and clip, potential equalization bolt; transformer for potential-isolation from the mains Certification pending. Product launch planned for Q3 2024.
degree of protection:	appliance class I (⊕) / type B (A) / IP 20
classification:	medical device risk class IIb according to MDR, active therapeutic medical device and active diagnostic medical device
usage class:	S, I according to ISO 20957-1
accuracy class:	A (high accuracy) according to ISO 20957-6
earth leakage current:	< 0.2 mA
ambient condition:	+10 ... +30 °C; (-30 ... +50 °C on request) 20 ... 85 % humidity (up to 100% on request) 700 ... 1060 hPa air pressure; 3,000 m (~10,000 ft) max. altitude without pressurization
display (resolutions) parameter:	7" TFT capacitive color touch display speed, time, elevation, distance, heart rate, heart rate variability
resolution:	1 decimal place
units:	metric
heart rate monitoring:	heart rate receiver included (5kHz + Bluetooth®), automatic control of speed and elevation according to programmed target heart rate („cardio mode“)
digital interface:	via optional „connect package“; optional Bluetooth®, NFC, RFID
programs:	Standard: Quick, Time, pulse („cardio mode“) optional program package: watt sensitive, therapy, interval, k-cal, hills, distance
PC software (incl.):	para control® for display & remote control
accessory (incl.):	instruction for use on media stick, service kit, 5m LAN cable, 5m PE-cable
colour of frame:	pure white RAL 9010 (powder coated)
handrails:	steel tube handrails diameter 60 mm on both sides, over min. 1/3 of treadmill length, easily exchangeable Other handrail designs optional at extra charge.
voltage supply:	200 ... 240 Volt AC 1~/N/PE 50/60 Hz 16A fuse; dedicated circuit, line and protection
size of frame:	L x W x H: 210 cm x 86cm x 126cm (6ft 11" x 2ft 9.9" x 4ft 1.6")
mass of device:	device approx. 240 kg (530 lbs)
mass of packaging:	75 ... 265 kg (165 ... 585 lbs) depending on requirement

E & OE. Subject to alterations without prior notice. The illustrations may show accessories and items of optional equipment which are not part of standard specification or the recommended configuration. Subject to our general terms of trade: www.hpcosmos.com
Weight and dimensions may differ depending on accessories.

Optionally available at extra charge are special frame colours, other handrail designs, special voltage supply, other options and accessories. Weight and package specifications can deviate according to options, accessories packing and way of transport. E&OE. Subject to alterations without prior notice. Please consider the natural and physical performance limitations of the single phase 230 volt power supply. The single phase 230 volt power supply is sufficient up to normal fitness or therapy applications. For all special high performance applications (speed running, controlled jump-ons, sidesteps, heavy subjects at higher speed, extreme elevations, etc.), we recommend models with a 3-phase, 3x400 volt power supply ((for example model h/p/cosmos quasar® med 3p, pulsar® 3p, venus® or saturn®).

Warning! Installation, commissioning, instruction, maintenance and repair work only to be conducted by h/p/cosmos trained and authorized personnel. For treadmills with oversized deck (width >65cm), for children, special applications, without sufficient safety space behind the treadmill, for subjects and / or patients with health or other limitations (e.g. visual impairment, etc.), for running at high speed and / or for all individuals, where a fall triggers a dangerous risk of injury or death (e.g. newly operated hip patients, invasive probes, etc.), a fall prevention system is obligatory (e.g. safety arch with chest belt and harness or a weight support system). For more information see the instructions for use. Safety space behind the treadmill: min. L: 2 m (6ft 6.74") x treadmill width. Children are only allowed to be on the treadmill, if under permanent supervision and secured by a fall prevention system.




specifications pluto® ef sport 900 Certification pending. Product launch planned for Q4 2024.

treadmill	pluto® ef sport
manufacturer:	h/p/cosmos sports & medical gmbh / Germany
order number:	cos31011
applications:	endurance training walking and running
control:	UserTerminal with easy-to-use 7" TFT – capacitive touch display, via integrated interface coscom® v4
running surface:	L x W: 150 x 50 cm (4' 11.1" x 1' 7.6") access height: 23 cm (9.1") - shock load reduction for the joints - running belt with slip resistant surface - max. permissible load: 250 kg (551 lbs) - max. permissible load: 300 kg (660 lbs) at extra charge
speed range:	0.0 ... 22.0 km/h (0.0 ... 6.1 m/s) (0.0 ... 13.7 mph) special speed available at extra charge
acceleration:	1 acceleration / deceleration level
elevation:	0 ... 25 % (0 ... 14.0°) motorized adjustment (-25 % ... +25 % when using optional reverse belt rotation)
running direction:	reverse belt rotation at extra charge. Without fall prevention the max. speed for reverse belt rotation is limited to 5 km/h (3.1 mph)
motor systems:	2.2 kW (3 HP) 3-phase AC motor, maintenance free and brushless For high-performance applications we recommend models with a 3-phase 3x400 Volt power supply and a running surface min. 190/65 cm
power transmission:	frequency inverter, poly-V-belt, very quiet operation
safety systems:	CE machinery regulation (EU) 2023/1230; EN 60335-1; EN 60601-1-2 (EMC tested); ISO 20957-1; ISO 20957-6; EN 14971; emergency-stop mushroom push button (drives power off) emergency stop switch (safety lanyard with actuator, pull cord and clip) Certification pending. Product launch planned for Q3 2024.
degree of protection:	appliance class I (⊕) / IP 20
classification:	sports and fitness device; not for medical, not for therapeutic applications
usage class:	S, I according to ISO 20957-1
accuracy class:	A (high accuracy) according to ISO 20957-6
earth leakage current:	< 2.5 mA
ambient condition:	+10 ... +30 °C (-30 ... + 50°C on request) 20 ... 95 % humidity, (up to 100% on request) 700 ... 1060 hPa air pressure 3,000 m (~10,000 ft) max. altitude without pressurization
display (resolutions) parameter:	7" TFT capacitive color touch display speed, time, elevation, distance, heart rate, heart rate variability
resolution:	1 decimal place
units:	metric
heart rate monitoring:	heart rate receiver included (5kHz + Bluetooth®), automatic control of speed and elevation according to programmed target heart rate („cardio mode“)
digital interface:	via optional „connect package“; optional Bluetooth®, NFC, RFID
programs:	Standard: Quick, Time, pulse („cardio mode“) optional program package: watt sensitive, therapy, interval, k-cal, hills, distance
PC software (incl.):	para control® for display & remote control
accessory (incl.):	instruction for use on media stick, service kit, 5m lan cable
colour of frame:	pure white RAL 9010 (powder coated)
handrails:	steel tube handrails diameter 60 mm on both sides, over min. 1/3 of treadmill length, easily exchangeable Other handrail designs optional at extra charge.
voltage supply:	200 ... 240 Volt AC 1~/N/PE 50/60 Hz 16A fuse; dedicated circuit, line and protection
size of frame:	L x W x H: 210 cm x 86cm x 126cm (6ft 11" x 2ft 9.9" x 4ft 1.6")
mass of device:	approx. 225 kg (495 lbs)
mass of packaging:	75 ... 265 kg (165 ... 585 lbs) depending on requirements


E & OE. Subject to alterations without prior notice. The illustrations may show accessories and items of optional equipment which are not part of standard specification or the recommended configuration.
Subject to our general terms of trade: www.hpcosmos.com
Weight and dimensions may differ depending on accessories.

Optionally available at extra charge are special frame colours, other handrail designs, special voltage supply, other options and accessories. Weight and package specifications can deviate according to options, accessories packing and way of transport. E&OE. Subject to alterations without prior notice. Please consider the natural and physical performance limitations of the single phase 230 volt power supply. The single phase 230 volt power supply is sufficient up to normal fitness or therapy applications. For all special high performance applications (speed running, controlled jump-ons, sidesteps, heavy subjects at higher speed, extreme elevations, etc.), we recommend models with a 3-phase, 3x400 volt power supply (for example model h/p/cosmos quasar® med 3p, pulsar® 3p, venus® or saturn®).

Warning! Installation, commissioning, instruction, maintenance and repair work only to be conducted by h/p/cosmos trained and authorized personnel. For treadmills with oversized deck (width >65cm), for children, special applications, without sufficient safety space behind the treadmill, for subjects and / or patients with health or other limitations (e.g. visual impairment, etc.), for running at high speed and / or for all individuals, where a fall triggers a dangerous risk of injury or death (e.g. newly operated hip patients, invasive probes, etc.), a fall prevention system is obligatory (e.g. safety arch with chest belt and harness or a weight support system). For more information see the instructions for use. Safety space behind the treadmill: min. L: 2 m (6ft 6.74") x treadmill width. Children are only allowed to be on the treadmill, if under permanent supervision and secured by a fall prevention system.



space for your notes:



sports / athletics



sports
quasar®



cycling & athletics
saturn® med 300/100r



performance diagnostics
pulsar® med 3p



inline skating
saturn® med 300/125r



functional training
pulsar® med 3p + robowalk®



cross country skiing
skating / biathlon
saturn® med 450/300rs



wheelchair
saturn® med 300/125r



speed training / speedlab®
quasar® 3p



fitness
pluto® / mercury® / quasar® / pulsar®



motion analysis
quasar® med



expander training
robomove®



bike ergometer
torqualizer®



biomechanics
gait parameters
optogait

rehabilitation



active gait correction
robowalk® expander / mercury® med



senior fitness
mercury®



orthopaedic rehabilitation
mercury® med / arm support / airwalk® ap



cardiac rehabilitation
mercury® med



body weight supported
treadmill therapy
airwalk® ap / mercury® med



angiology
mercury® med



gait analysis / biomechanics
gaitway® 3d with force and
pressure measurement



cardiovascular stress
testing / CPET
mercury® med



locomotion therapy
locomotion® med 150/50



bike ergometer
torqualizer® 1200
medical certification pending

special applications



environmental & climate
chambers
quasar® med 3p with
external UserTerminal



biomechanics
gaitway® 3d



military / army
quasar® special version



speed training
sprint trainer comet®



fire fighter ladder
training & fitness
discovery®

h/p/cosmos dealer contact:

manufacturer

h/p/cosmos sports & medical gmbh
Am Sportplatz 8
83365 Nussdorf-Traunstein
Germany

phone: +49 86 69 86 42 0
fax: +49 86 69 86 42 49

sales@hpcosmos.com
www.hpcosmos.com

skype: @hpcosmos.com (search & select name)
youtube: youtube.com/hpcosmos
twitter: twitter.com/hpcosmos
facebook: facebook.com/hpcosmos



© 05/2024 h/p/cosmos [cos/1-en-to-01] Errors and omissions excepted. h/p/cosmos is certified according to EN 13485 for medical treadmills. All technical data, descriptions, equipment variants and illustrations of devices, options are non-binding, in particular do not represent warranted characteristics and can deviate from offer and delivery. The Bluebird®, Windows®, NFC and further word marks and logos are registered trademarks. All word marks, logos and trademarks are the property of their respective owners.